


POWER SUPPLY

FEATURES

- Rugged Construction
- UL, CSA, CE Certified
- Some Models Provide Built-In Redundancy
- Wide Input Voltage Ranges
- Compact Package
- Wide Operating Temperature Range
- DIN Rail Mountable



POWER SUPPLY UNIT ON OPENLINE® SYSTEM

SPECIFICATIONS

General

Terminal Blocks:

J2: 1 row of 6 for internal bus power (Mating connector not included³)

J3: 1 row of 3 for AC input. (Mating plug included)

J4: 1 row of 4 for auxiliary loads (Mating plug included)

Terminals Screw Torque: 7-9 in-lbs

Bus Output: +5V output can be run in parallel with other bus supplies.

SPECIFICATIONS

Specification	74-PWR-AC1	74-PWR-AC2	74-PWR-AC3
Input Voltage Range:	85-250 Vac	85-250 Vac	85-250 Vac
Input Frequency Range:	47-440 Hz	47-440 Hz	47-440 Hz
Input Current:	1.5A @ 115 Vac	1.0A max. (RMS) @115 Vac	1.0A max. (RMS) @115 Vac
Output Voltage Ranges:	4.8 to 5.2 Vdc, -4.8 to -5.2 Vdc,	4.8 to 5.2 Vdc, 11.7 to 12.9 Vdc, & -11.7 to 12.9 Vdc	4.8 to 5.2 Vdc 11.7 to 12.9 Vdc, & -11.7 to -12.9 Vdc
Maximum Output Current ¹ :	7.0A @ 0-40°C derate 2.5% per degree 40-70°C	3.0A @ 0-40°C, derate 2.5% per degree 40-70°C	5.0A @ 0-40°C, derate 2.5% per degree 40-70°C
Minimum Load Current:	0A @	0.3A @ 5 Vdc	0A
Secondary Output Current ² :	NA	NA	NA
Efficiency:	70% typical	70% typical at full load	70% typical at full load
Ripple:	<50 mV	<50 mV	<50 mV
Indicator:	1 green power supply OK LED ⁴	1 green power supply OK LED ⁴	1 green power supply OK LED ⁴
Conductor Size:	(1) 14 AWG or (2) 16 AWG	(1) 14 AWG or (2) 16 AWG	(1) 14 AWG or (2) 16 AWG
Protection:	3.15A @ 250 Vac fuse, overload and reverse polarity protection.	2.0A @ 250 Vac fuse, overload and reverse polarity protection.	2.0A @ 250 Vac fuse, overload and reverse polarity protection.

¹ Output current rating assumes horizontal DIN rail or panel mounting, no cover, and no auxiliary air flow. For horizontal mounting with cover, current rating is specified from 0 to 30°C, derate 2.5% per degree 30 to 70°C. For vertical mounting with cover, current rating is derated 15% from 0 to 30°C, derate additional 2.5% per degree from 30 to 60°C.

² -5V output current is derived from +5V output using a DC-DC converter with 75% efficiency. Therefore, +5V output maximum current is derated by 1.33 x -5V output current.

³ PC mount mating plug connector Phoenix Contact type MSTB 2.5/6-G-5.08.

⁴ Power LED will pulse on and off if min. load requirement for proper regulation is not met.

